

TECHNICAL DATA SHEET

Update of this document : 14/10/16
ISO reference : DON/LS 03.4244.A



LEMAITRE SECURITE SAS
17 rue Bitschhoffen
CS 90024

F 67350 La Walck FRANCE

Tél. : +33 (0)3 88 72 28 80

Fax : +33 (0)3 88 07 05 37

www.lemaitre-securite.com

contact@lemaitre-securite.com



SIROCCO ROAD SBP HI HRO SRA

High shoe in water-repellent
full grain leather and
hydrocarbons resistant



PROTECTIONS FOR THIS MODEL



Sizes available from 39 (6) to 47 (12)
Weight of one pair in size 42 (8): 1400 gr.
Norm EN ISO 20345 : 2011

Upper features

- Upper : water-repellent full grain leather
- Tongue with gusset : leather
- Collar : synthetic
- Lining : three-dimensional textile
- Vamp lining : synthetic
- Backpart : synderm
- Closing : lace
- Eyelets and loop : plastic
- Tongue marking : size, manufacturer, manufacture date (month, year), norm, protection, CE marking

Fitting features

- Lasting insole : high tenacity composite fabric
- Insock : textile and foam

Sole features

- Name : C07
- Material : Polyurethane / Nitrile
- Comfort sole color : dark grey
- Outsole color : black

Protections 0% METAL

- Toecap : polycarbonate (200 joules)
- Anti-perforation insert : high tenacity composite fabric « 0 » penetration (1100 N)

Advantages = End users benefits

Highly insulated model minimizing the temperature rise into shoes during the laying of asphalt.

- **Leather 2,0 mm thickness** for a better mechanical resistance (abrasion, tear, perforation) and durability.
- **Water-repellent full grain leather and hydrocarbons resistant.**
- **Tongue with gusset in leather.**
- **Three-dimensional micro-porous textile as lining** : High breathable thanks to its structure that allows better ventilation of sweat. It is flexible and it improves comfort.
- **Anti-perforation insert high tenacity composite fabric** : ultra-light, ultra-flexible (insensitive to worn), thermally insulating (insensitive to temperature transfers) and protects 100% of the surface of the foot.
- **Composite toecap** made of injected polycarbonate, ergonomic, light, elastic and thermic insulation (not sensitive to variation and heat transfer between -10°C to 40°C).
- **C07 - PU / Nitrile sole**
 - ✓ Comfort sole : Injected polyurethane
 - ✓ Outsole : Rubber nitrile
 - ✓ Special lightly grooved non-marking sole
 - ✓ No heel on the outsole
 - ✓ No drawing on sides: completely smooth sole

Basics and additional requirements of the norm EN ISO 20345 : 2011

Toecap

steel polycarbonate aluminium HDFC Fiber composite

- Antistatic footwear.
- Penetration resistance.
- Resistance of the outsole to hot contact.
- Water penetration and water absorption resistant upper.
- Energy absorption of seat region.
- Heat insulation of sole complex.
- Metatarsal protection.

Anti-perforation insert

stainless steel composite (high tenacity fabric)

- Resistance of the outsole to fuel oil.
- Cold insulation of sole complex.
- Water resistant footwear.

Regarding the norm EN ISO 20345, the minimum results for slip resistance to get the SRC certificate are :
SRA (flat) ≥ 0,32 SRB (flat) ≥ 0,18
SRA (heel) ≥ 0,28 SRB (heel) ≥ 0,13



=

+